

FTKR1000 SERIES



Operating Condition

- Max. Pressure : 15kg/cm² , Max. Temperature : 180°C
- Max. Rotation Speed : 15A~40A : 300RPM , 50A~80A : 150RPM
- Media : Steam, Hot Oil, Water

Features

- Enables low friction & high speed operation at high temperature & pressure
- Bellows inside, enables switching between cooling & heating operation

FTKR2200 SERIES



Operating Condition

- Max. Pressure : 10kg/cm² , Max. Temperature : 100°C
- Max. Rotation Speed :
6A~25A : 1000RPM, 32A~40A : 700RPM, 50A~80A : 500RPM
- Media : Water, Air, Gas, Oil

Features

- Enables low friction & high speed rotation at high pressure
- Corrosion resistance (Brass body, Stainless shaft/spring)

FTKR3000 SERIES / FTKR3200 SERIES



Operating Condition

- Max. Pressure : 15kg/cm² , Max. Temperature : 220°C
- Max. Rotation Speed : 15A~25A : 300RPM , 32A~100A : 150RPM
- Media : 3000 Series : Steam, 3200 Series : Hot Oil

Features

- Spherical Sealing, Two Carbon Bearing (Non-Lubrication)
- Self-supported & Alignment rotating union

FTKR3700 SERIES




Operating Condition

- Max. Pressure : 15kg/cm² , Max. Temperature : 220°C
- Max. Rotation Speed : 15A~25A : 300RPM , 32A~100A : 150RPM
- Media : Steam, Hot Oil

Features

- Spherical Sealing, Two Carbon Bearing (Non-Lubrication)
- Self-supported & Alignment rotating union
- High temp, steam & hot oil media

FTKR4000 SERIES



Operating Condition

- Max. Pressure : 15kg/cm² , Max. Temperature : 220°C
- Max. Rotation Speed : 50A~100A : 300RPM , 125A~150A : 150RPM
- Media : Steam, Hot Oil

Features

- Dual Spherical Sealing, Self-Alignment rotating
- Enables low friction & high speed rotation
- Non-lubrication type

- Customized specifications available.
- Please avoid Max. pressure at Max. speed(rpm) in operation.